



## SAFETY DATA SHEET

### SAS450 (Hardener)

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name SAS450 (Hardener)

Container size 25ml

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Two-component, epoxy-based adhesive.

##### 1.3. Details of the supplier of the safety data sheet

Supplier Nina Works,  
Gelderd Road,  
Leeds  
LS12 6NA  
Tel: +44 (0) 113 213 4300

##### 1.4. Emergency telephone number

Emergency telephone +44 (0) 113 213 4300

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

##### 2.2. Label elements

###### Pictogram



Signal word

Danger

Hazard statements

H302+H332 Harmful if swallowed or if inhaled.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

## SAS450 (Hardener)

### Precautionary statements

P260 Do not breathe vapour/ spray.  
 P261 Avoid breathing vapour/ spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a POISON CENTER/ doctor if you feel unwell.  
 P321 Specific treatment (see medical advice on this label).  
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P363 Wash contaminated clothing before reuse.  
 P391 Collect spillage.  
 P405 Store locked up.  
 P501 Dispose of contents/ container in accordance with national regulations.

### Contains

Triethylene Glycol Dimercaptan, N(3-dimethylaminopropyl)-1,2-propylenediamine

### 2.3. Other hazards

#### Other hazards

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>Triethylene Glycol Dimercaptan</b> CAS number: 14970-87-7	<b>60-100%</b>
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H332	
<b>N(3-dimethylaminopropyl)-1,2-propylenediamine</b> CAS number: 10563-29-8	<b>10-30%</b>
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317	

**SAS450 (Hardener)**

<b>Terphenyl</b>	<b>10-30%</b>
CAS number: 26140-60-3	
M factor (Acute) = 1	M factor (Chronic) = 1
<b>Classification</b> Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

<b>Inhalation</b>	Remove person to fresh air and keep comfortable for breathing. If breathing stops, provide artificial respiration. For breathing difficulties, oxygen may be necessary. Get medical attention if symptoms are severe or persist.
<b>Ingestion</b>	Do not induce vomiting unless under the direction of medical personnel. Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Get medical attention if symptoms are severe or persist.
<b>Skin contact</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water. Wash clothing and clean shoes thoroughly before reuse. Get medical attention if symptoms are severe or persist.
<b>Eye contact</b>	Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention. If in doubt, get medical attention promptly.

**4.2. Most important symptoms and effects, both acute and delayed**

<b>General information</b>	The product contains a sensitising substance.
<b>Inhalation</b>	May be harmful if inhaled.
<b>Ingestion</b>	Harmful if swallowed.
<b>Skin contact</b>	Causes burns. May cause sensitisation by skin contact. May cause skin sensitisation or allergic reactions in sensitive individuals.
<b>Eye contact</b>	Causes serious eye irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

<b>Specific treatments</b>	Treat symptomatically.
----------------------------	------------------------

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

<b>Suitable extinguishing media</b>	Water spray, foam, dry powder or carbon dioxide.
-------------------------------------	--

**5.2. Special hazards arising from the substance or mixture**

<b>Hazardous combustion products</b>	Oxides of carbon. Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO). Oxides of nitrogen.
--------------------------------------	--

**5.3. Advice for firefighters**

<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

**SECTION 6: Accidental release measures**

## SAS450 (Hardener)

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8.

### 6.2. Environmental precautions

**Environmental precautions** To prevent release, place container with damaged side up. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Provide adequate ventilation. Eliminate all sources of ignition. Clear up spills immediately and dispose of waste safely. Absorb spillage with sand or other inert absorbent. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid contact with skin, eyes and clothing. Do not breathe gas, fume, vapours or spray. Do not eat, drink or smoke when using this product. Keep container tightly closed and at temperature not exceeding 23°C. Wash hands thoroughly after handling.

**Hygiene measures:**

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep container tightly closed and at temperature not exceeding 23°C. Keep container tightly sealed when not in use.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Terphenyl

Short-term exposure limit (15-minute): WEL 0.5 ppm 4.8 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

### 8.2. Exposure controls

**Appropriate engineering controls** As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

**Eye/face protection** Wear chemical splash goggles.

**Other skin and body protection** Wear appropriate clothing to prevent skin contamination.

**Respiratory protection** If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

## SAS450 (Hardener)

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colourless.
Odour	Strong.
pH	Not applicable.
Melting point	Not available.
Initial boiling point and range	>149°C @
Flash point	≥ 157°C COC (Cleveland open cup).
Evaporation rate	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	Not available.

#### 9.2. Other information

Other information	No information required.
-------------------	--------------------------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

#### 10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

#### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise.
------------------------------------	----------------------

#### 10.4. Conditions to avoid

Conditions to avoid	Keep away from heat, sparks and open flame.
---------------------	---

#### 10.5. Incompatible materials

Materials to avoid	Oxidising agents. Acids - oxidising. Acids - non-oxidising.
--------------------	---

#### 10.6. Hazardous decomposition products

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - oral

ATE oral (mg/kg)	555.55555556
------------------	--------------

##### Acute toxicity - inhalation

ATE inhalation (vapours mg/l)	12.22222222
-------------------------------	-------------

### SECTION 12: Ecological Information

## SAS450 (Hardener)

**Ecotoxicity** Very toxic to aquatic life with long lasting effects. The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### 12.1. Toxicity

**Ecotoxicity**

### 12.2. Persistence and degradability

**Persistence and degradability** There are no data on the degradability of this product.

### 12.3. Bioaccumulative potential

**Partition coefficient** Not available.

### 12.4. Mobility in soil

**Mobility** No data on possible environmental effects have been found.

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## SECTION 14: Transport information

### 14.1. UN number

**UN No. (ADR/RID)** 1760

**UN No. (IMDG)** 1760

**UN No. (ICAO)** 1760

**UN No. (ADN)** 1760

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** CORROSIVE LIQUID, N.O.S.

**Proper shipping name (IMDG)** CORROSIVE LIQUID, N.O.S.

**Proper shipping name (ICAO)** CORROSIVE LIQUID, N.O.S.

**Proper shipping name (ADN)** CORROSIVE LIQUID, N.O.S.

### 14.3. Transport hazard class(es)

**ADR/RID class** 8

**ADR/RID classification code** C9

**ADR/RID label** 8

**SAS450 (Hardener)**

IMDG class 8

ICAO class/division 8

ADN class 8

**Transport labels****14.4. Packing group**

ADR/RID packing group II

IMDG packing group II

ADN packing group II

ICAO packing group II

**14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant

No.

**14.6. Special precautions for user**

EmS F-A, S-B

ADR transport category 2

Emergency Action Code 2X

Hazard Identification Number 80  
(ADR/RID)

Tunnel restriction code (E)

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code****SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).  
 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
 Dangerous Preparations Directive 1999/45/EC.

VOC content (2010/75/EC)

**15.2. Chemical safety assessment****Inventories****EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

**US - TSCA 12(b) Export Notification**

None of the ingredients are listed or exempt.

**SECTION 16: Other information**

## SAS450 (Hardener)

Revision date	30/08/2016
SDS number	5298
Hazard statements in full	H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H332 Harmful if inhaled. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.


**PRECAUTIONS:** This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product.

**WARRANTY:** All products purchased from or supplied by Van-Line are subject to terms and conditions set out in the contract. Van-Line warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Van-Line is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Van-Line makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.



**SAFETY DATA SHEET****SAS450 (Resin)**

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Product name** SAS450 (Resin)**Container size** 25ml**1.2. Relevant identified uses of the substance or mixture and uses advised against****Identified uses** Two-component, epoxy-based adhesive.**1.3. Details of the supplier of the safety data sheet****Supplier** Nina Works,  
Gelderd Road,  
Leeds  
LS12 6NA  
Tel: +44 (0) 113 213 4300**1.4. Emergency telephone number****Emergency telephone** +44 (0) 113 213 4300**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification (EC 1272/2008)****Physical hazards** Not Classified**Health hazards** Eye Irrit. 2 - H319 Skin Sens. 1 - H317**Environmental hazards** Aquatic Chronic 2 - H411**2.2. Label elements****Pictogram****Signal word** Warning**Hazard statements** H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

## SAS450 (Resin)

### Precautionary statements

P261 Avoid breathing vapour/ spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P321 Specific treatment (see medical advice on this label).  
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337+P313 If eye irritation persists: Get medical advice/ attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P391 Collect spillage.  
 P501 Dispose of contents/ container in accordance with national regulations.

### Contains

Epoxy Resin (Epichlorohydrin, Bisphenol A), Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

### 2.3. Other hazards

#### Other hazards

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>Epoxy Resin (Epichlorohydrin, Bisphenol A)</b> CAS number: 25085-99-8	<b>60-100%</b>
<b>Classification</b> Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	
<b>Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol</b> CAS number: 9003-36-5      EC number: 500-006-8	<b>5-10%</b>
<b>Classification</b> Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air and keep comfortable for breathing. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Get medical attention if symptoms are severe or persist.

#### Ingestion

Do not induce vomiting unless under the direction of medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms are severe or persist.

## SAS450 (Resin)

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. Wash clothing and clean shoes thoroughly before reuse. Get medical attention if symptoms are severe or persist after washing.

**Eye contact** Get medical attention if irritation persists after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation** May cause respiratory irritation.

**Ingestion** No specific symptoms known.

**Skin contact** May cause an allergic skin reaction. Irritating to skin.

**Eye contact** Causes eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Water spray, foam, dry powder or carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

**Hazardous combustion products** Oxides of carbon. Aldehydes Organic acids Acrid smoke or fumes.

### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use suitable respiratory protection if ventilation is inadequate. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.

### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. To prevent release, place container with damaged side up.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** If leakage cannot be stopped, evacuate area. Provide adequate ventilation. Absorb spillage with sand or other inert absorbent. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## SAS450 (Resin)

**Usage precautions** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin, eyes and clothing. Do not breathe gas, fume, vapours or spray. Do not eat, drink or smoke when using this product.

**Hygiene measures:**

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Do not store near heat sources or expose to high temperatures. Store in tightly-closed, original container in a dry, cool and well-ventilated place.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

### 8.2. Exposure controls

**Appropriate engineering controls** As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

**Eye/face protection** Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear chemical splash goggles.

**Other skin and body protection** Wear appropriate clothing to prevent repeated or prolonged skin contact.

**Respiratory protection** Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Colour</b>	Clear.
<b>Odour</b>	Mild.
<b>pH</b>	Not applicable.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	260°C/500°F @
<b>Flash point</b>	≥ 249°C/480°F PMCC (Pensky-Martens closed cup).
<b>Evaporation rate</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.

### 9.2. Other information

**Other information** None.

## SECTION 10: Stability and reactivity

## SAS450 (Resin)

### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Will not polymerise.

### 10.4. Conditions to avoid

**Conditions to avoid** Keep away from heat, sparks and open flame.

### 10.5. Incompatible materials

**Materials to avoid** Oxidising agents. Strong acids. Amines.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Aldehydes. Organic acids

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicological effects** No data recorded.

## SECTION 12: Ecological Information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

### 12.1. Toxicity

**Ecotoxicity**

**Toxicity** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Partition coefficient** Not available.

### 12.4. Mobility in soil

**Mobility** No information available

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

## SECTION 14: Transport information

## SAS450 (Resin)

### 14.1. UN number

3082

### 14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (Epoxy Resin Number average MWC &lt;= 700)

### 14.3. Transport hazard class(es)

9

#### Transport labels



### 14.4. Packing group

III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS F-A, S-F

Emergency Action Code 32

Hazard Identification Number 90  
(ADR/RID)

Tunnel restriction code (E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78  
and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments.

Dangerous Preparations Directive 1999/45/EC.

VOC content (2010/75/EC)

### 15.2. Chemical safety assessment

## SAS450 (Resin)

### Inventories

#### EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

#### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

### SECTION 16: Other information

Revision date	30/08/2016
SDS number	5299
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.

**PRECAUTIONS:** This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product.

**WARRANTY:** All products purchased from or supplied by Van-Line are subject to terms and conditions set out in the contract. Van-Line warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Van-Line is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Van-Line makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.